

# TECH LINE COATINGS, INC.



26844 ADAMS AVE. ♦ MURRIETA, CA 92562 ♦ USA

Phone 951-304-0498

♦ Fax 951-461-9658

www.techlinecoatings.com

## MATERIAL SAFETY DATA SHEET

### SECTION I

**COMMON NAME(S):** MCX

**CHEMICAL NAME(S) AND SYNONYM(S):** ALUMINUM FILLED METALLIC CERAMIC COATING

**CHEMICAL FAMILY:** Not Applicable

**FORMULA:** Complex Mixture

**EMERGENCY PHONE:** (Chemtrec) 1-800-424-9300

**INFORMATION PHONE:** 951-304-0498

**DATE PREPARED:** 8/13/2003 (update)

### SECTION II

<u>HAZARDOUS INGREDIENTS</u>	<u>CAS#</u>	<u>CONCENTRATIONS</u>
------------------------------	-------------	-----------------------

ALUMINUM POWDER ACGIH TLV: 10mg/M3	7429-90-5	<25%
---------------------------------------	-----------	------

PHOSPHATE/CHROMATE SOLUTION (Less than 3.% of total weight is CrO3) ACGIH TLV: 1mg/M3	92203-02-6	>15%
---	------------	------

NOTE: The National Toxicology program lists chromium and certain chromium compounds to be carcinogenic.

### SECTION III

#### PHYSICAL CHARACTERISTICS

**BOILING POINT:** N/A

**VAPOR DENSITY (AIR = 1):** <1

**% VOLATILE VOLUME:** 59.7%

**APPEARANCE AND ODOR:** GRAY GREEN WITH NO ODOR

**SOLUBILITY IN WATER:** APPRECIABLE

**VOC'S:** 0

**SHIPPING:** Non Hazardous

### SECTION IV

#### FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** NONE

**EXTINGUISHING MEDIA:** USE SAND OR CARBON DIOXIDE

**SPECIAL FIRE FIGHTING PROCEDURES:** DO NOT USE EXTINGUISHING AGENTS CONTAINING WATER, AS REACTION WITH ALUMINUM MAY PRODUCE HYDROGEN GAS.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** CONTACT WITH ALKALIS, STRONG REDUCING OR OXIDIZING AGENT MAY PRODUCE HYDROGEN GAS, CAUSING FIRE OR EXPLOSION HAZARD.

### SECTION V

#### REACTIVITY DATA

**STABILITY:** STABLE

**INCOMPATIBILITY (MATERIALS TO AVOID):** CONTACT WITH OXIDIZING AGENTS, ALKALIS OR STRONG REDUCING AGENTS

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR

### SECTION VI

#### HEALTH HAZARD DATA

**ROUTES OF ENTRY:**

INHALATION ? YES

SKIN ? YES

INGESTION ? YES

**CARCINOGENICITY:**

NTP, OSHA ? CHROMIUM AND CERTAIN CHROMIUM COMPOUNDS ARE LISTED

**HEALTH HAZARDS:**

**EYES:** CAUSES SEVERE IRRITATION

**SKIN:** CAUSES MILD SKIN IRRITATION, DRYING OF SKIN

**INHALATION:** MAY CAUSE DRYING OF NASAL AND RESPIRATORY TISSUE

**INGESTION:** HARMFUL IF SWALLOWED, CAUSING VOMITING, NAUSEA, DIARRHEA

**EMERGENCY AND FIRST AID:**

**EYES:** IMMEDIATELY FLUSH WITH PLENTY OF WATER, CALL A PHYSICIAN

**SKIN:** WASH WITH WATER. REMOVE CONTAMINATED CLOTHING

**INHALATION:** REMOVE INDIVIDUAL TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. CALL A PHYSICIAN

**INGESTION:** GIVE LARGE AMOUNTS OF WATER FOLLOWED BY MILK OF MAGNESIA. CALL A PHYSICIAN IMMEDIATELY

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** RESPIRATORY, DERMAL AILMENTS

**SECTION VII**

**SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** CLEAN SPILL WITH ABSORBENT MATERIAL. NEUTRALIZE WITH SODIUM BICARBONATE. DO NOT USE STRONG ALKALIS. FLUSH AREA WITH WATER

**WASTE DISPOSAL METHOD:** MATERIAL MAY BE BAKED AT CURE TEMPERATURE THEN DISCARDED AS SOLID WASTE, OR FILTER TO REMOVE ALUMINUM AND DISCARD AS SOLID WASTE. TREAT REMAINING LIQUID WITH SODIUM METABISULFITE, THEN PRECIPITATE TRIVALENT CHROMIUM BY NEUTRALIZING WITH ALKALI, SUCH AS LIME. DISPOSAL SHOULD BE MADE IN ACCORD WITH FEDERAL, STATE AND LOCAL REGULATIONS.

**SECTION VIII**

**SPECIAL PROTECTION / CONTROL MEASURES:**

**RESPIRATORY PROTECTION:** #9910 RESPIRATOR MANUFACTURED BY 3M OR EQUIVALENT

**VENTILATION:**

**LOCAL EXHAUST:** USE TO MAINTAIN BELOW TWA LIMITS

**MECHINICAL:** USE NON-SPARKING EQUIPMENT

**PROTECTIVE GLOVES:** RUBBER ACID PROOF

**EYE PROTECTION:** SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

**OTHER PROTECTIVE EQUIPMENT:** WEAR PROTECTIVE CLOTHING, ACID PROOF

**WORK / HYGIENIC PRACTICES:** WASH THOROUGHLY AFTER HANDLING PRODUCT AND BEFORE EATING, DRINKING OR SMOKING

**SECTION IX**

**SPECIAL PRECAUTIONS**

**HANDLING AND STORAGE:** STORE IN AREAS THAT WILL NOT COME INCONTACT WITH STRONG ALKALIS OR OXIDIZING AGENTS.

**NOTE:** Since this compound contains aluminum powder, a clean spray area and duct system are important. It is hazardous to allow an accumulation of dried material to occur since this dried material in the form of duct could be ignited by sparks or other means and possibly cause a dust explosion as with any finely divided powdered material.

---

**THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF TECH LINE COATINGS, INC., KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY TECH LINE COATINGS, INC. TO BE ACCURATE, AND TECH LINE COATINGS, INC., DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME. BEFORE USING ANY CHEMICAL, READ ITS LABEL, INSTRUCTIONS AND MATERIAL SAFETY DATA SHEET.**