

TECH LINE COATINGS, INC.



26844 Adams Ave. ♦ MURRIETA, CA 92562 ♦ USA
Phone 951-304-0498
♦ Fax 951-461-9658
www.techlinecoatings.com

MATERIAL SAFETY DATA SHEET

SECTION I

COMMON NAME (S): GEL-TECH lubricants UGX
CHEMICAL NAME (S) AND SYNONYM (S): GREASE
CHEMICAL FAMILY: N/A
FORMULA: N/A
EMERGENCY PHONE: (Chemtrec) 1-800-424-9300
INFORMATION PHONE: 951-304-0498
DATE PREPARED: 5/1/2002 (update)

SECTION II

HAZARDOUS INGREDIENTS

<u>COMPONENT</u>	<u>CAS#</u>	<u>TLV/PEL</u>
HYDROTREATED NAPHTHENIC DISTILLATES OSHA PEL: 5mg/m ³	64742-52-5	ACGIH TLV: 10mg/m ³
ALUMINUM HYDROXIDE BENZOATE STEARATE OSHA PEL: 10mg/m ³	54326-11-3	ACGIH TLV: 10mg/m ³
MOLYBDENUM DISULFIDE OSHA PEL: 10 mg/m ³	1317-33-5	ACGIH TLV: 10 mg/m ³

SECTION III

PHYSICAL CHARACTERISTICS

BOILING POINT: 600F
VAPOR DENSITY (AIR = 1): NOT APPLICABLE
VAPOR PRESSURE: NOT APPLICABLE
MELTING POINT: 475F
APPEARANCE AND ODOR: BLACK GREASE, BLAND ODOR
SOLUBILITY IN WATER: NIL
REACTIVITY IN WATER: NOT APPLICABLE
SPECIFIC GRAVITY (H₂O = 1): 0.89

SECTION IV

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 460F (D-92)
FLAMMABLE LIMITS: NOT APPLICABLE
LEL-
UEL-
DOT: NO LABELING REQUIRED
EXTINGUISHING MEDIA: FOAM, CO₂, DRY CHEMICAL. USE WATER SPRAY TO COOL SURFACE OF CONTAINER

SPECIAL FIRE FIGHTING PROCEDURES: USE FULL PROTECTIVE EQUIPMENT, INCLUDING SELF CONTAINED BREATHING APPARATUS TO PREVENT INHALATION OF FUMES, VAPORS OR MISTS THAT MAY BE GENERATED DURING FIRE FIGHTING ACTIVITIES. WATER MAY CAUSE FROTHING.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

OTHER INFORMATION: AVOID CONTACT WITH FIRE AND SPARKS

SECTION V

REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID) : CONTACT WITH STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: CO & CO₂ IF IN COMPLETE COMBUSTION. OXIDES OF CARBON AND SULFUR.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: OPEN FLAMES

SECTION VI

HEALTH HAZARD DATA

ROUTES OF ENTRY:

INHALATION? YES

SKIN? YES

INGESTION? YES

TOXICITY (ACUTE AND CHRONIC) MILD (TRANSIENT)

CARCINOGENICITY: NONE

SIGNS AND SYMPTOMS OF EXPOSURE: NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE

EMERGENCY AND FIRST AID:

EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER, CALL A PHYSICIAN (FLUSH FOR AT LEAST 15 MIN., INCLUDING UNDER EYELIDS)

SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING GET MEDICAL ATTENTION IF NECESSARY.

INHALATION: REMOVE TO FRESH AIR. SEE PHYSICIAN IF NECESSARY

INGESTION: DO NOT INDUCE VOMITING, DRINK PLENTY OF WATER. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. SEE PHYSICIAN IMMEDIATELY.

SECTION VII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE OR CONTAIN SPILL. APPLY ABSORBANT. PUT IN CONTAINER, CLOSE CONTAINER. PREVENT FROM GOING INTO SEWER AND WATERWAYS. NOTIFY PROPER AUTHORITIES. OBEY LOCAL, STATE AND FEDERAL REGULATIONS.

WASTE DISPOSAL METHOD: FREE LIQUIDS MAY NOT BE LANDFILLED. RECOVER AND/OR INCINERATE LIQUIDS WHERE POSSIBLE. DISPOSAL SHOULD BE MADE IN ACCORD WITH FEDERAL, STATE AND LOCAL REGULATIONS.

OTHER PRECAUTIONS: NOT DOT REGULATED

SECTION VIII

SPECIAL PROTECTION / CONTROL MEASURES:

RESPIRATORY PROTECTION: USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR IF TWA/TLV LIMITS ARE EXCEEDED

VENTILATION:

LOCAL EXHAUST: USE TO MAINTAIN BELOW TWA LIMITS

MECHANICAL: USE NON-SPARKING EQUIPMENT

PROTECTIVE GLOVES: NEOPRENE GLOVES RECOMMENDED IF CONTACT IS LIKELY

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS, FACE SHIELD OR GOGGLES

OTHER PROTECTIVE EQUIPMENT: ADEQUATE TO AVOID SKIN CONTACT

WORK / HYGIENIC PRACTICES: WASH THOROUGHLY AFTER HANDLING PRODUCT AND BEFORE EATING, DRINKING OR SMOKING.

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF TECH LINE COATINGS, INC., KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY TECH LINE COATINGS, INC. TO BE ACCURATE, AND TECH LINE COATINGS, INC., DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME. BEFORE USING ANY CHEMICAL, READ ITS LABEL, INSTRUCTIONS AND MATERIAL SAFETY DATA SHEET.